



LEFFELECTRIC

magnum cable

216.432.3000

MULTI-PAIR, INDIVIDUALLY SHIELDED, NON-PLENUM

NEC Type CM and/or CL2

22 AWG CONDUCTORS

PART NUMBER	NO. OF PAIRS	AWG. SIZE	CONDUCTOR STRAND.	NOM. INSUL. THK. INCHES	NOM. JKT. WALL INCHES	NOM. OD. INCHES	WEIGHT PER MFT.
A20067	2	22	7/30	0.008	0.020	0.165	18.7
A20069	3	22	7/30	0.010	0.032	0.292	43.6
A20075	6	22	7/30	0.010	0.032	0.381	77.8

18 AWG CONDUCTORS

PART NUMBER	NO. OF PAIRS	AWG. SIZE	CONDUCTOR STRAND.	NOM. INSUL. THK. INCHES	NOM. JKT. WALL INCHES	NOM. OD. INCHES	WEIGHT PER MFT.
A20077	2	18	16/30	0.016	0.032	0.345	65.0

PRODUCT CONSTRUCTION

Conductor

- Stranded or solid bare copper
ASTM B-33

Insulation

- Premium grade color-coded PVC

Shield

- Overall polyester supported aluminum foil with drain wire, plus a stranded tinned copper to facilitate grounding

Jacket

- Premium grade PVC
- Suitable for use from -20°C to +60°C
- Suggested voltage rating of 300 volts

APPLICATIONS

- When total isolation is required in computers
- Point-of-Sales (POS) equipment
- Remote and industrial equipment control circuits

COMPLIANCES

- Listed by UL as type CM and/or CL2 cables for use in NEC Article 800 and/or 725 installations
- OSHA acceptable