



# LEFFELECTRIC

magnum cable

216.432.3000

## MULTI-PAIR, INDIVIDUALLY SHIELDED, NON-PLENUM

### NEC Type CM and/or CL2

#### 22 AWG CONDUCTORS

PART NUMBER	NO. OF PAIRS	AWG. SIZE	CONDUCTOR STRAND.	NOM. INSUL. THK. INCHES	NOM. JKT. WALL INCHES	NOM. OD. INCHES	WEIGHT PER MFT.
A20067	2	22	7/30	0.008	0.020	0.165	18.7
A20069	3	22	7/30	0.010	0.032	0.292	43.6
A20075	6	22	7/30	0.010	0.032	0.381	77.8

#### 18 AWG CONDUCTORS

PART NUMBER	NO. OF PAIRS	AWG. SIZE	CONDUCTOR STRAND.	NOM. INSUL. THK. INCHES	NOM. JKT. WALL INCHES	NOM. OD. INCHES	WEIGHT PER MFT.
A20077	2	18	16/30	0.016	0.032	0.345	65.0

### PRODUCT CONSTRUCTION

#### Conductor

- Stranded or solid bare copper  
ASTM B-33

#### Insulation

- Premium grade color-coded PVC

#### Shield

- Overall polyester supported aluminum foil with drain wire, plus a stranded tinned copper to facilitate grounding

#### Jacket

- Premium grade PVC
- Suitable for use from -20°C to +60°C
- Suggested voltage rating of 300 volts

### APPLICATIONS

- When total isolation is required in computers
- Point-of-Sales (POS) equipment
- Remote and industrial equipment control circuits

### COMPLIANCES

- Listed by UL as type CM and/or CL2 cables for use in NEC Article 800 and/or 725 installations
- OSHA acceptable